

Datasheet Gel Type VRLA Batteries

6V 180Ah

1. Physical Data

Box Data

Battery		CHG		Lid	max	basic	max	basic	Lid	max	Weight	
Type	V	C ₅	cond. Series	Ter- minal	Colour Box	length [mm]	length [mm]	width [mm]	width [mm]	height [mm]	height [mm]	[kg]
GF	06	180	V			244	244	190	190	253	275	31
GF	06	180	V	P		244	244	190	190	253	275	32
GF	06	180	V	Q		244	244	190	190	253	282	33

max. height w. covered M8 srew type connectors

282 mm

Tightening Torque Values of connectors to Terminal

conical terminal according EN 60095-2

8 ± 1Nm

Female M8/M10-bolted

20 ± 1Nm

2. Performance Data

Discharge rate	Capacity	End Of DCH Voltage DOD		Effective DCH Time DOD		Energy Density		Power Density	
		60%	80%	60%	80%	[Wh/l]	[Wh/kg]	[W/l]	[W/kg]
[h]	[Ah]	[V]		[h]		[Wh/l]	[Wh/kg]	[W/l]	[W/kg]
20,0	200,0	2,01	1,98	10,8	14,4	102,8	38,9	5,1	1,9
10,0	190,0	2,00	1,97	5,7	7,6	97,2	36,8	9,7	3,7
5,0	180,0	1,98	1,93	3,0	4,0	90,2	34,1	18,0	6,8
3,0	168,0	1,96	1,89	1,9	2,6	83,8	31,7	27,9	10,6
2,0	154,0	1,93	1,78	1,4	1,9	74,8	28,3	37,4	14,2
1,0	130,0	1,90	1,63	0,8	1,0	61,8	23,4	61,8	23,4
0,5	109,5	1,57	1,57	0,5	0,5	50,7	19,2	101,4	38,4
0,2	81,6	1,40	1,40	0,2	0,2	37,4	14,1	186,8	70,7

Typical values after 20 - 50 C₅ cycles at 30°C

recommended max. Load *)

360 A

*) With appropriate counter contacts only

Cyclic endurance according IEC 254-1

700

Temperature Regime (Depending on DOD)

-20 °C up to 50 °C

Typical Operational Temperature Regime

5 °C up to 40 °C

3. Charging

Charging Profile(s)

IUIa

according EXIDE Technologies Specification

Fast Charge

Possible

We reserve the right to discontinue or change specification any time without notice or obligation